



TECHNICAL SPECS

Schäffer
Model 24e



	DIMENSIONS	24e
A	Wheelbase	5 ft 9.1 in
B	Chassis length	10 ft 10.7 in
C	Overall length with standard bucket	13 ft 3.3 in
D	Digging depth	4.1 in
E	Max. working height	10 ft 7.2 in
F	Max. bucket pivot height	8 ft 2.4 in
G	Loading height with pallet fork	7 ft 8.9 in
H	Max. dumping height	5 ft 6.9 in
I	Front end height	4 ft 10.7 in
J	Dumping depth	10.2 in
K	Seat height	3 ft 9.7 in
L	Overhead guard height Cab height	7 ft 2.2 in 7 ft 0.3 in
N	Overall width	40.2 - 61.8 in
O	Inner turning radius	4 ft 3.6 in
P	Outer turning radius	7 ft 7.7 in
Q	Outer radius with standard bucket	8 ft 10.7 in

TECHNICAL DATA	24e
Engine	Drive: 28.2 hp Working hydraulics: 13 hp
Drive unit	4-wheel-drive, fully electric
Battery	Lithium-Ion, 260 V; 6.7 kWh or 13.4 kWh
Charging system	On board charger, 3 kW/230 V/16 A Option: ext. charging system, 18 kW/400 V/32 A
Service braking system/parking brake	Multi-disc brake running in oil bath
Working hydraulics output/pressure	Delivery rate: 11.1 GPM Operating pressure: 2,611 psi
Steering	Fully hydraulic articulated/swivel steering
Operating weight	4,883 lbs with protective roof 5,027 lbs with cab
Lifting capacity	4,189 lbs
Tipping load, straight ¹ Pallet fork Bucket	3,549 lbs 3,726 lbs
Tipping load, articulated ¹ Pallet fork Bucket	2,513 lbs 3,241 lbs
Payload Pallet fork, even ground ² Pallet fork, uneven ground ² Bucket ³	2,011 lbs 1,508 lbs 1,620 lbs
Axles	Original Schäffer axles, 6 wheel nut rim
Speed	12.4 mph
Electric system	Operating voltage: 12 V
Fill quantities	Hydraulic oil: 3.2 gal
Sound pressure level LpA	64 dB(A)

¹ acc. to ISO 8313 ² acc. to EN 474-3 ³ acc. to ISO 14397-1

Tire dimensions and additional equipment can change the operating weight, tipping load, and payload.

Wheel Options (Standard tire option highlighted in yellow)

DIMENSION	LOADER WIDTH (in)*	TREAD OPTIONS
10.0/75-15.3	40.2 (47.2) - 43.3**	MPT, AS Farmer, SKD, M159
27x10.5-15.5	40.6 (46.5)**	SKD
31x15.5-15	50.8	SKD, AS Farmer, Allground
31x15.5-15***	53.9	Allground, AS Farmer, SKD
31x13.50-15***	59.8	Multi Trac
10.0x75-15.3***	50.4 - 53.9	AS Farmer, SKD, MPT

*Measurements vary based on rim offset configurations.

**Measurements in brackets for width with turned wheels.

***Wide axle only.



SKD



AS FARMER



ALLGROUND



MPT



MULTI TRAC